



等边角管

製作区分	型番	形状寸法 (mm)				断面積 (mm <sup>2</sup> )	单重 (kg / m)	材質区分			
		A	T	R 1	R 2			I	II	III	IV
A	S 19785	19.15	1.5	1	-	105	0.284		○		
A	FC 54	20	2	-	-	144	0.388	○			
A	U 47007	40	1.5	1.5	-	229.1	0.618		○		
A	SJ 1039	40	3	0.5	-	443.8	1.198	○			
A	SJ 1052	50	3	2	-	560.6	1.514	○			
A	S 61961	60	3	3	1	677	1.828		○		
A	SJ 1079	60	4	5	5	896	2.419	○	○		
A	HS 153	96	3	9	6	1077.4	2.909	○			
A	SJ 1078	96	3	9	6	1077.4	2.909	○			
A	SJ 1053	100	3	2	2	1164	3.143	○			
G	G 25515	15	1.5	-	-	81	0.219		○		
G	G 25505	19	1	-	-	72	0.194		○		
G	G 25507	20	1.5	-	-	111	0.300		○		
G	G 25514	20	2	-	-	144	0.389		○		
G	G 25501	25	1.5	-	-	141	0.381		○		
G	G 25506	25	2	-	-	184	0.497		○		
G	G 25511	25	2.5	-	-	225	0.608		○		
G	G 25502	30	2	-	-	224	0.605		○		
G	G 25513	30	3	-	-	324	0.875		○		
G	G 25517	40	2.5	-	-	375	1.013		○		
G	G 25519	40	3	-	-	444	1.199		○		
G	G 25508	50	3	-	-	564	1.523		○		
N	S 11107	10	2.5	-	-	75	0.203		○		
N	S 17340	12.7	1.4	-	-	63	0.170		○		
N	S 48016	14	1.5	-	-	75	0.203				○
N	U 10002	15	1.5	2	1	78	0.211		○		
N	S 45045	18	2.0	2.5	2	126	0.340		○		○
N	U 10003	19	1.6	3	1.4	105	0.284		○		
N	U 10005	19	2	2	2	136	0.367		○		○
N	U 20004	20	1.5	2	1	108	0.292		○		
N	U 20005	20	2	1	1	144	0.389		○		○
N	U 20003	20	2	4	2	134	0.362				○
N	U 20009	25	3	1 以下	-	263.5	0.711		○		
N	S 41112	25.4	2.5	2	1	226	0.610		○		○
N	U 30001	30	2	2	0.5	221	0.597		○		○

